

> HIGH BRIGHTNESS < > LOW CONSUMPTION < > RESISTANCE TO VIBRATIONS <















DRAWINGS, DIMENSIONS **AND WEIGHTS**







ELYPS LM S I PART NO -

allCOLOR	allCLEAR	
32371	32381	
32372	32382	
32373	32383	
32374	32384	
32375	32385	
32376	32386	

ELYPS LM S

LIGHT MODULE

Integrated bright LED steady light module.

With its clear colors and simple functionality, ELYPS LM S is the right choice for a high performance stacklight module.

ELYPS LM S offers versatility and good optical as performance as well virtually maintenance thanks to the built-in technology that guarantees up to 100.000* hours of product life.

Available with allCOLOR and allCLEAR lens.

ELYPS LM S is the right choice for a high performance stacklight module.

* At normal conditions, without vibrations and heavy temperature changes

KEY CHARACTERISTICS

LIGHT EFFECTS

STEADY

VOLTAGES

According to selected Wiring Module (WM)
With WM LT and WM LT MULTI: 12/24V ACDC With WM HT and WM HT MULTI: 120/240V AC

PROTECTION GRADE

IP65, suitable for outdoor applications

OPERATING TEMPERATURE

-30/+50 C°

MECHANICAL FEATURES

Self extinguishing PC body with high resistance, suitable for outdoor use thanks to the IP65 protection grade

OPTICAL FEATURES

6x Bright LEDs (3 per side). The vertically lined lens allows a perfect light distribution over 360°. Available with 2 different lens types, according to the final application

allCOLOR

STANDARD USE

Colored lens with colored light source.
The use of a colored lens with the same-color light source allows optimization of the emission frequency producing a rich intense light output

allCLEAR

USE IN VERY BRIGHT ENVIRONMENTS

Clear lens with colored light source. In very bright environments it is possible that the ambient brightness lights up the module when it is switched OFF creating problems in distinguishing between the ON and OFF state of the stacklight (phantom effect). The clear lens module allows clear distinction between the ON and OFF status of the stacklight



alcolor

allCLEAR

CERTIFICATIONS

