



BABYSAI LED



> 100 dB max <
> with LED LIGHT <



BABYSAI LED | PART NO

	GY	BK	RD
12V DC	37801	37811	37821
24V DC	37802	37812	37822
48V DC	37803	37813	37823
12V AC	37805	37815	37825
24V AC	37806	37816	37826
48V AC	37807	37817	37827
110V AC	37808	37818	37828
240V AC	37809	37819	37829

BABYSAI LED

Compact-size horn with LED light engineered for industrial applications.

Developed with acoustic electromagnetic capsule with vibrating membrane, the device generates a characteristic continuous sound.

Ideal choice for industrial applications, short call or danger signals.

KEY CHARACTERISTICS

NUMBER OF TONES

1 (Continuous Sound)

VOLTAGES

12V DC, 24V DC, 48V DC +/-10%
12V AC, 24V AC, 48V AC, 110V AC, 240V AC +/-10%

PROTECTION GRADE

IP43

OPERATING TEMPERATURE

-30/+40 °C

MECHANICAL FEATURES

ABS body and sound speaker

Provided with flat base. Screw mounting (screws not included)

ACOUSTIC FEATURES

Electromagnetic unit with vibrating membrane

Continuous sound:


DC versions: 650+/-50Hz

AC versions: 300/7000Hz

OPTICAL FEATURES

6 red LEDs producing steady light

DRAWINGS, DIMENSIONS AND WEIGHTS



BABYSAI LED



CERTIFICATIONS

