

RELAY INTERFACE MODULES

41F Series

6mm Wide Single Pole Relay Interface Modules

41F Single Pole 6A Module with built in LED & Ejector Clip



Product Code	Supply Voltage	Relay Type	Relay Voltage	Socket Type	Socket Voltage
41F-1Z-C2-5-9VDC	9VDC	HF41F009ZS	9VDC	41F-1Z-C2-5	5-24VDC
41F-1Z-C2-5-12VDC	12VDC	HF41F012ZS	12VDC	41F-1Z-C2-5	5-24VDC
41F-1Z-C2-5-24VDC	24VDC	HF41F024ZS	24VDC	41F-1Z-C2-5	5-24VDC

41F Accessories

- Change Over Contacts
- Supplied complete, Relay, and Socket
- 1 Part Number for simple ordering
- Sensitive Coils
- 35mm Din Rail mounting
- Compact 6mm Wide Design
- Other Coil Voltages available on request

Product Code	Description
41F-20	20 Way Jumper Bar
41F-TAG	Sheet of 64 Identification Tags
41F-S	Plastic Separator

Contact Data	
Contact Arrangement	1C
Contact Rating	6A 250VAC
Max. Switching Power	1500VA / 180W
Contact Resistance	100mΩ (at 1A 6VDC)
Contact Material	AgNi
Electrical Life	30,000 Ops
Mechanical Life	10,000,000 Ops

Relay Characteristics	
Insulation Resistance	1000MΩ
Dielectric Strength:	
Between Coil & Contacts	4000VAC 1Min
Between Open Contacts	1000VAC 1Min
Operate Time	8ms Max.
Release Time	4ms Max.
Ambient Temperature	-40°C to 55°C

Approved by:



Outline Dimensions

