






> SUPERBRIGHT < > TWO MULTIFUNCTIONAL VERSIONS <



ACCESSORIES



WALL BASE

MAXIFLASH LED FLR | PART NO

	Blue	Orange	Red	Green	Yellow	White
GY	12/24V ACDC 43001 43002	43003	43004	43005	43006	
	90/240V AC 43011 43012	43013	43014	43015	43016	
BK	12/24V ACDC 43021 43022	43023	43024	43025	43026	
	90/240V AC 43031 43032	43033	43034	43035	43036	

MAXIFLASH LED SLR | PART NO

	Blue	Orange	Red	Green	Yellow	White
GY	12/24V ACDC 43041 43042	43043	43044	43045	43046	
	90/240V AC 43051 43052	43053	43054	43055	43056	
BK	12/24V ACDC 43061 43062	43063	43064	43065	43066	
	90/240V AC 43071 43072	43073	43074	43075	43076	
SPARE DOMES	71321 71320	71323	71324	71334	71322	

GY	WALL BASE	72692
BK	WALL BASE	71872

MAXIFLASH LED new

Multifunctional LED beacon with high optical performance engineered for industrial applications.

Developed with a multichannel technology, MAXIFLASH is available in FLR (steady, flashing, rotating light) or in SLR (flashing, strobe, random light) version. The separate light effects are controllable via independent electric contacts.

MAXIFLASH LED offers maximum versatility: a perfect fit for each applications.

KEY CHARACTERISTICS

LIGHT EFFECTS

MAXIFLASH LED FLR: STEADY, FLASHING, ROTATING LIGHT

MAXIFLASH LED SLR: FLASHING, STROBE, RANDOM LIGHT

VOLTAGES

MAXIFLASH LED FLR: 12/24V ACDC, 90/240V AC +/-10%

MAXIFLASH LED SLR: 12/24V ACDC, 90/240V AC +/-10%

PROTECTION GRADE
IP54

OPERATING TEMPERATURE
-30/+50 °C

MECHANICAL FEATURES

Self-extinguishing high impact resistance PC dome

Self-extinguishing glass reinforced polyamide base with M16 cable gland

Screw mounting, screws not included

OPTICAL FEATURES

MAXIFLASH LED FLR: 24x Bright LEDs in a 6x4 configuration allow 3 luminous effects:

STEADY LIGHT: A deep and rich light source

FLASHING LIGHT: A single flash (1F)

ROTATING LIGHT: A unique rotating effect perfectly simulating the traditional rotating beacons yet without moving parts hence enormously enhancing product life time

MAXIFLASH LED SLR: 2x SuperBright LEDs allow 3 luminous effects:


FLASHING LIGHT: Powerful flashing effect (1F)

STROBE LIGHT: Strobe effect (5F)

RANDOM LIGHT: A unique random effect consisting in an uneven flashing pattern, augmenting the ability of catching attention

The dome-shaped Fresnel lens intensify the luminous beam of these devices

DRAWINGS, DIMENSIONS AND WEIGHTS



MAXIFLASH LED FLR
MAXIFLASH LED SLR



CERTIFICATIONS

