

EX 165 SIAD EX 165 SIADEL



EX 215 SIAD EX 215 SIADEL



EX 265 SIAD EX 265 SIADEL



SIAD / SIADEL

V		12	24	48	110	240
A		1	0.5	0.3	0.1	0.06
dB						
Hz						

IP 66	On	°C -20 +50
		M25x1.5

CODES	12V	24V	48V	110V	240V
EX 165 SIAD	62258	62259	62260	62261	62262
EX 165 SIADEL	62273	62274	62275	62276	62277
EX 215 SIAD	62263	62264	62265	62266	62267
EX 215 SIADEL	62278	62279	62280	62281	62282
EX 265 SIAD	62268	62269	62270	62271	62272
EX 265 SIADEL	62283	62284	62285	62286	62287

SPARE STRIKER 165
SPARE STRIKER 215
SPARE STRIKER 265

84080
84081
84082

SIAD SIADEL

Explosion-proof bells available in three dimensions: 165, 215 and 265 mm. Specifically designed and made according to the highest quality standards, these products guarantee a sound level that meets the most demanding customer requirements making the SIAD - SIADEL range one of the most effective on the market.


Explosion-proof bells for use in Group II areas, Zones 1, 2 explosive atmospheres.



II 2G Ex d e IIC T6


- Approval: **CESI 10 ATEX 042 X**
- Housing in copper-free aluminium alloy
- Polyester paint RAL 3020
- Voltages available:
 - SIAD: 12V-24V-48V-110V-240V AC
 - SIADEL: 12V-24V-48V-110V-240V DC
- Audibility: max. 100 dB(A)1m
- Protection: IP 66
- Maximum surface temperature: T6

165




Kg: 2.32

215



Kg: 2.95

265



Kg: 3.78