

DESCRIPTION

Fixed male fitting in nickel-plated brass suitable for flexible and foldable metal conduits.


Max IP degree of the system IP69 using BTP accessory



Code	Description
6014-20A	Metal Gland M20 Thread For Ø15.5mm internal Conduit
6014-25A	Metal Gland M25 Thread For Ø20.5mm internal Conduit
6014-32A	Metal Gland M32 Thread For Ø26.5mm internal Conduit
6014-4035	Metal Gland M40 Thread For Ø35mm internal Conduit
6014-40A	Metal Gland M40 Thread For Ø40mm internal Conduit
6014-50A	Metal Gland M50 Thread For Ø50.5mm internal Conduit
6014-6350	Metal Gland M50 Thread For Ø50.5mm internal Conduit

66BTP IP RAISER JACKET

Made of thermoplastic material, free of halogen, silicon and cadmium substances.
 This solution increases the level of tightness to IP66/ IP68/IP69 in coupling between fittings and flexible metal with vacuum coating.
 It can be used with fittings of series 60 and 61.
 Electrical continuity guaranteed.



Code	Description
66BTP16	Sealing For Ø15.5mm Conduit IP44 To IP69
66BTP22	Sealing For Ø20.5mm Conduit IP44 To IP69
66BTP32	Sealing For Ø26.5mm Conduit IP44 To IP69
66BTP38	Sealing For Ø35mm Conduit IP44 To IP69
66BTP40	Sealing For Ø40mm Conduit IP44 To IP69
66BTP50	Sealing For Ø50.5mm Conduit IP44 To IP69