




ROTALLARM S




> 3 LUMINOUS SOURCES <
> EXCELLENT OPTICAL PERFORMANCE <




ROTALLARM S H1




ROTALLARM S




ROTALLARM S STEADY/FLASHING



ROTALLARM S FLASHING H1



ROTALLARM S X



ALSO AVAILABLE



ROTALLARM S
STEADY/FLASHING
ROTALLARM S X

ROTALLARM S

The most successful rotating beacon in Sirena's history, engineered for industrial applications.

Available with 3 luminous sources ROTALLARM S offers versatility as well as a complete range of products.

KEY CHARACTERISTICS

LIGHT EFFECTS

ROTALLARM S and ROTALLARM S H1: ROTATING LIGHT

ROTALLARM S STEADY/FLASHING: STEADY/FLASHING LIGHT

ROTALLARM S FLASHING H1: FLASHING LIGHT

ROTALLARM S X: XENON FLASHING LIGHT

VOLTAGES

ROTALLARM S: 12V ACDC, 24V ACDC, 48V DC, 48V AC, 110V AC and 240V AC +/-10%

ROTALLARM S H1: 12V ACDC, 24V ACDC +/-10%

ROTALLARM S STEADY/FLASHING: 12/48V DC, 24/240V AC +/-10%

ROTALLARM S FLASHING H1: 12V ACDC, 24V ACDC +/-10%

ROTALLARM S X: 12/24V ACDC, 110V AC and 240V AC +/-10%

PROTECTION GRADE

IP65

OPERATING TEMPERATURE

-30/+50 °C | X: -30/+40 °C

MECHANICAL FEATURES

Self-extinguishing high impact resistance PC dome

Self-extinguishing PC/ABS base with M20 cable gland

Screw mounting, screws not included

Parallel axis gear drive (rotating version ROTALLARM S and ROTALLARM S H1)

OPTICAL FEATURES

ROTALLARM S: anodized aluminium reflector with BA 15s 45W bulb (for 12V ACDC, 24V ACDC, 48V DC versions) or E14 25W bulb (for 48V AC, 110V AC and 240V AC versions)

ROTALLARM S H1: anodized aluminium reflector with H1 55W (12V) or 70W (24V) halogen bulb

ROTALLARM S STEADY/FLASHING: 40W Incandescent lamp with Ba 15d socket

ROTALLARM S FLASHING H1: H1 55W (12V) or 70W (24V) halogen bulb

ROTALLARM S X: Xenon discharge tube 6J, allows a high intensity single flash (1F)

CERTIFICATIONS



ACCESSORIES



P BASE


Base for pole mounted installations (Ø 48,5) with 2 retaining dowels. Recommended for use with black base product.

GRID for P BASE




WALL BASE


DRAWINGS, DIMENSIONS AND WEIGHTS



ROTALLARM S



ROTALLARM S + GRID + P BASE



ROTALLARM S + P BASE



ROTALLARM S* - Rotating beacon with incandescent bulb

	GY	BK	GY	BK	GY	BK	GY	BK	GY	BK	GY	BK
12V ACDC	63001	82002	63002	82001	63003	82004	63004	82005	63005	82095	63006	82003
24V ACDC	63013	82012	63014	82011	63015	82014	63016	82015	63017	82097	63018	82013
48V DC	63025	82083	63026	82080	63027	82081	63028	82074	63029	82082	63030	82084
48V AC	63031	82078	63032	82076	63033	82075	63034	82046	63035	82077	63036	82034
110V AC	63037	82027	63038	82026	63039	82029	63040	82030	63041	82098	63042	82028
240V AC	63049	82042	63050	82041	63051	82044	63052	82045	63053	82035	63054	82043

*Supplied with bulb

ROTALLARM S H1* - Rotating beacon with halogen bulb

	GY	BK	GY	BK	GY	BK	GY	BK	GY	BK	GY	BK
12V ACDC	63055	82051	63056	82050	63057	82053	63058	82054	63059	82092	63060	82056
24V ACDC	63066	82061	63067	82060	63068	82063	63069	82064	63070	82093	63071	82062

*Supplied with bulb

ROTALLARM S STEADY/FLASHING* - Steady/flashing light with incandescent bulb

	GY	BK	GY	BK	GY	BK	GY	BK	GY	BK	GY	BK
12/48V DC	89451	89471	89452	89472	89453	89473	89454	89474	89455	89475	89456	89476
24/240V AC	89461	89481	89462	89482	89463	89483	89464	89484	89465	89485	89466	89486

*Supplied without bulb

ROTALLARM S FLASHING H1* - Flashing light with halogen bulb

	GY	BK	GY	BK	GY	BK	GY	BK	GY	BK	GY	BK
12V ACDC	82401	80051	82402	80050	82403	80053	82404	80054	82405	80094	82406	80052
24V ACDC	82421	80061	82422	80060	82423	80063	82424	80064	82425	80093	82426	80062

*Supplied with bulb

ROTALLARM S X* - Flashing light with Xenon discharge tube

	GY	BK	GY	BK	GY	BK	GY	BK	GY	BK	GY	BK
12/24V ACDC	85411	85471	85412	85472	85413	85473	85414	85474	85415	85475	85416	85476
110V AC	85421	85481	85422	85482	85423	85483	85424	85484	85425	85485	85426	85486
240V AC	85431	85491	85432	85492	85433	85493	85434	85494	85435	85495	85436	85496

*Supplied with bulb

SPARE DOMES ROTALLARM S and H1

Internally smooth	71306	71305	71308	71309	71331	71307
-------------------	-------	-------	-------	-------	-------	-------

SPARE DOMES ROTALLARM S STEADY/FLASHING and X

Internally fluted	71301	71300	71303	71304	71330	71302
-------------------	-------	-------	-------	-------	-------	-------

ACCESSORIES

	STL	GY	BK
P BASE for ROTALLARM S			83005
GRID for P BASE	90883		
WALL BASE		72692	71872