



G B R W

> 115 dB <  
> 64 TONES <  
> 2 LEVELS OF ALARM <



#### CAN BE INSTALLED WITH

G B R W

See Base Section on page 30

	SHALLOW	DEEP	WALL
12/24V ACDC	✓	✓	✓
PNP 12/24V DC	✗	✗	✓
40/80V ACDC	✗	✓	✓
120/240V AC	✗	✓	✓
JR 120/240V AC	✗	✗	✓
	FLUSH	DOUBLE	POLE

#### SIR-E MAX | PART NO

G 90407 B 90408 R 90410 W 90409

## SIR-E MAX new

Multifunctional high-output electronic siren developed with a multichannel technology that allows two separate levels of alarm (pre-alarm, alarm) controllable via independent electric contacts. SIR-E MAX benefits from 64 different tones (selectable via dip-switch) over 2 channels.

### TECHNICAL SPECIFICATIONS

#### MULTIFUNCTION

2 levels of alarm (pre-alarm, alarm) controllable via independent electric contacts

#### HIGH ACOUSTIC PERFORMANCE

##### CHANNEL 1 | PRE-ALARM

A powerful up to 115 dB electronic tone, ideal for alerting staff of a danger or a serious change of operating circumstances (tone selectable via dip switch "A" out of 32 tones)

##### CHANNEL 2 | ALARM

A powerful up to 115 dB electronic tone, ideal for alerting staff of a permanent change of operating circumstances (tone selectable via dip switch "B" out of 32 tones)

#### ADJUSTABLE VOLUME

Min. 65 dB

#### MULTITONE

64 tones available, including fire alarm, industrial and civil tones

#### VOLTAGES

According to the installed base

#### PROTECTION GRADE

IP65, TYPE 3R (pending), suitable for outdoor applications

#### OPERATING TEMPERATURE

-30/+50 °C

### MECHANICAL FEATURES

Self extinguishing PC body with high impact resistance, suitable for outdoor applications thanks to the IP65/TYPER 3R (pending) protection grade

### CERTIFICATIONS



### DRAWINGS, DIMENSIONS AND WEIGHTS

