



90742



Combined Sounder & Beacon Cold Room Application



Designed for use in Cold Rooms, the Sirena SIR-E combined Sounder & Beacon is constructed to withstand temperatures as low as -30°C and up to +50°C.



V AC/DC	12-24 V	
50/60Hz		
mA (max)	360	340
mA (min)	70	80
dB(A)1m	100	

ATTRIBUTES





TONE SWITCH A

No	Tone	dB(A)1m	F(Hz)	Times	Description	Dipswitch
1	LF Sweep	94	800 - 1000	Cycle 0.5s	CF LOW FREQUENCY SWEEP	0 0 0
2	Bi-Tone	92	480 - 610	0.5s / 0.5s	EVACUATION 1	1 0 0
3	Linear	90	610	-	EVACUATION 2	0 1 0
4	Bi-tone	94	600 - 700	0.5s / 0.5s	STANDARD	1 1 0
5	Multi-tone	94	1000 - 1700	Cycle 0.25s	STANDARD	0 0 1
6	Sweep	98	500 - 1200	3.5s ON / 0.5s OFF	NETHERLANDS-NEN2575:2000	1 0 1
7	Bi-tone	93	970 - 630	0.5s / 0.5s	APOLLO FIRE SYSTEM BS5839	0 1 1
8	Sweep	95	1200 - 500	Cycle 1s	DIN 33 404	1 1 1

TONE SWITCH B

No	Tone	dB(A)1m	F(Hz)	Times	Description	Dipswitch
1	Intermittent	92	660	0.5s ON / 0.5s OFF	GENERAL PURPOSE	0 0 0
2	Bi-tone	94	600 - 700	0.5s / 0.5s	GENERAL PURPOSE	1 0 0
3	Modulated	98	1000 - 1700	Cycle 0.8s	STANDARD	0 1 0
4	Bi-tone	88	440 - 560	0.565s / 0.565s	STANDARD - EVACUATION	1 1 0
5	Linear	88	300	-	GENERAL PURPOSE	0 0 1
6	Linear	90	500	-	GENERAL PURPOSE	1 0 1
7	Bi-tone	90	510 - 610	1s / 1s	GENERAL PURPOSE	0 1 1
8	Intermittent	88	544	0.63s ON / 0.63s OFF	GENERAL PURPOSE	1 1 1

DIMENSIONS



Celebrating 40 years in the supply & distribution
of high quality Control & Automation Products.

t: 01785 818600 f: 01785 811900 e: sales@switchtec.com

www.switchtec.com



Switchtec

AUTOMATION | CONTROL | ELECTRONICS

E. & O. E