

LIGHT

IP54 JUNCTION BOXES

Description: IP54 WATERTIGHT JUNCTION BOX WITH KNOCK-OUT ENTRIES

Reference:

EX088

Characteristics:

Product type:	Watertight junction boxes with opaque cover and knock-out entries
Exterior dimensions (Height x Width x Depth):	89x89x52 mm
Dimensions of the flush-fit gap (HxWxD):	-
Number of modules:	-
Installation:	Surface
Color:	Grey RAL 7035
Window:	Opaque cover
Weight (Kg):	0,06
Cable entry:	7xM25
Components:	-
Materials:	Halogen-free plastic materials. Base and cover: Shock-proof PS

Technical data:

Degree of protection:	IP54
Resistance to impact:	IK07
Glow wire resistance:	650 °C
Ball pressure test:	70 °C
Ambient temperature range:	-25 °C / +40 °C
Maximum operating voltage:	1000 V AC / 1500 V DC
Double insulation:	Class II

Certificates and standards:

Directive:	2014/35/EU
Standards:	IEC 60998-2-5
Certificates:	



Codes:

EAN:	8431044182001
Customs tariff number:	85.38.10.00
ETIM 8.0:	EC002600

LIGHT

IP54 JUNCTION BOXES

Description: IP54 WATERTIGHT JUNCTION BOX WITH KNOCK-OUT ENTRIES

Reference: EX088



Detailed drawing:

 <http://www.ide.es/downloads/planos/pdf/EX088.pdf>

 <http://www.ide.es/downloads/planos/dxf/EX088.dxf>

 <http://www.ide.es/downloads/planos/stp/EX088.stp>

Exterior dimensions (Height x Width x Depth):

89x89x52 mm

Dimensions of the flush-fit gap (Height x Width x Depth):

-

Sustainability:

RoHS - REACH

Supply:

The boxes are supplied individually, shrink-wrapped and in multiple cardboard packaging, according to minimum packaging units.

Packaging units: 208

Product end of life:

It does not require specific recycling operations.

Recommended applications:

Industrial and outdoor environments. Industrial sites, docks, swimming pools, garages, anywhere that requires a high degree of protection against dust, splashes and impacts.