




Enclosed Switch Disconnectors

IS Series 2 Pole 25 Amp IP66 Enclosed DC Switch Disconnecter



- 25 Amp DC21B 510V
- 2 Pole (1 String)
- IP66 Weatherproof enclosure
- Padlockable in the off position
- Door interlocked handle
- Captive retained cover screws
- Conforms to IEC/EN 60947-3. UKCA & CE Approved
- Earth & Neutral terminals included
- 4 x M25 & 2 x M20 threaded cable entries
- Dimensions 160 x 85 x 113mm

Part Number	Description		
ISDC225	25 Amp 2 Pole IP66 Enclosed DC Switch Disconnecter		
Voltage	510VDC	600VDC	690VDC
Amps DC21B	25 Amp	23 Amp	19 Amp



TDCI-32 4 Pole 32 Amp 1000V IP66 Enclosed TRUE DC Switch Disconnecter




- 32 Amp DC21B 1000V
- 4 Pole On-Off (1 or 2 String)
- Supplied with bridging links
- IP66 Weatherproof enclosure
- -40°C to +85°C Operating Temperature
- Padlockable in the off position
- Door interlocked handle
- Captive retained cover screws
- Conforms to IEC/EN 60947-3 & UKCA/CE Approved
- Earth & Neutral terminals included
- 4 x M25 threaded cable entries

Part Number	Description
TDCI-32	32 Amp 1000V 4 Pole IP66 Enclosed DC Switch Disconnecter (Enclosure Dimensions 188 x 99 x 109mm)

2 Pole (4 Poles in Series) 1 String*

Voltage	Amperage DC21B
300VDC	32 Amp
500VDC	32 Amp
600VDC	32 Amp
800VDC	32 Amp
1000VDC	32 Amp

* Using bridging links provided



4 Pole (0 Pole in Series) 2 String

Voltage	Amperage DC21B
300VDC	32 Amp
500VDC	32 Amp
600VDC	13 Amp
800VDC	9 Amp
1000VDC	9 Amp

