

IS Series 3 & 4 Pole IP54 Metal Clad Enclosed Switch Disconnectors


- 20 to 100 Amp AC23A 690V
- 3 & 4 Pole
- IP54 Weatherproof enclosure
- Padlockable in the off position
- Door interlocked handle
- Captive retained cover screws
- Conforms to IEC/EN 60947-3. UKCA & CE Approved
- Earth & Neutral terminals included
- 4 x Cable Entries (20-40Amp M20)
(63-100Amp M25)

3 Pole IP54 Metal Clad Enclosed Switch Disconnectors

Part Number	440V AC23A	Description
ISMC320	5.5 Kw	20 Amp 3 Pole IP54 Metal Clad Switch Disconnectors (Enclosure Dimensions 147 x 111 x 122mm)
ISMC332	11 Kw	32 Amp 3 Pole IP54 Metal Clad Switch Disconnectors (Enclosure Dimensions 147 x 111 x 122mm)
ISMC340	15 Kw	40 Amp 3 Pole IP54 Metal Clad Switch Disconnectors (Enclosure Dimensions 220 x 144 x 132mm)
ISMC363	22 Kw	63 Amp 3 Pole IP54 Metal Clad Switch Disconnectors (Enclosure Dimensions 220 x 144 x 132mm)
ISMC380	30 Kw	80 Amp 3 Pole IP54 Metal Clad Switch Disconnectors (Enclosure Dimensions 270 x 220 x 151mm)
ISMC3100	37 Kw	100 Amp 3 Pole IP54 Metal Clad Switch Disconnectors (Enclosure Dimensions 270 x 220 x 151mm)

4 Pole IP54 Metal Clad Enclosed Switch Disconnectors

Part Number	440V AC23A	Description
ISMC420	5.5 Kw	20 Amp 4 Pole IP54 Metal Clad Switch Disconnectors (Enclosure Dimensions 147 x 111 x 122mm)
ISMC432	11 Kw	32 Amp 4 Pole IP54 Metal Clad Switch Disconnectors (Enclosure Dimensions 147 x 111 x 122mm)
ISMC440	15 Kw	40 Amp 4 Pole IP54 Metal Clad Switch Disconnectors (Enclosure Dimensions 220 x 144 x 132mm)
ISMC463	22 Kw	63 Amp 4 Pole IP54 Metal Clad Switch Disconnectors (Enclosure Dimensions 220 x 144 x 132mm)
ISMC480	30 Kw	80 Amp 4 Pole IP54 Metal Clad Switch Disconnectors (Enclosure Dimensions 270 x 220 x 151mm)
ISMC4100	37 Kw	100 Amp 4 Pole IP54 Metal Clad Switch Disconnectors (Enclosure Dimensions 270 x 220 x 151mm)

IS Series Auxiliary Contacts for AC Switches


- Side Mount Auxiliary Contact
- 1 Pole Normally Open + 1 Pole Normally Closed
- 20A rated contact
- Suitable for 3 & 4 Pole AC Switches Only
- CE Approved
- Conforms to IEC/EN 60947-3
- Max 2 Auxiliary contacts on 3 Pole Switches
- Max 1 Auxiliary contact on 4 Pole Switches

Part Number	Description
ISAUX-1	Size 1 Auxiliary Contact for 20A & 32A IS Series Switch Disconnectors
ISAUX-2	Size 2 Auxiliary Contact for 40A & 63A IS Series Switch Disconnectors
ISAUX-3	Size 3 Auxiliary Contact for 80A, 100A & 150A IS Series Switch Disconnectors