

TECHNICAL DATASHEET

SCL 3 POLE DC MINI CONTACTOR



- 9 - 16 Amp Mini Contactor
- AC3 IEC60947 - UL508
- Touchproof Terminals
- DIN Rail and Base Mount
- 3 pairs of Main Contacts
- 50/60Hz AC Coil
- 24V& 110V Coil
- 1 NO or 1 NC Auxiliary Contact
- Overload and additional accessories available



Part Number	Coil Voltage	AC3 Motor Rating	380-440V AC3	AC1 Amps	Aux Contact
MC09-10-3P-24VDC	24 VDC	9 Amp	4 Kw	20 Amp	1NO or 1NC
MC09-10-3P-110VDC	110 VDC	9 Amp	4 Kw	20 Amp	1NO or 1NC
MC12-10-3P-24VDC	24 VDC	12 Amp	5.5 Kw	20 Amp	1NO or 1NC
MC12-10-3P-110VDC	110 VDC	12 Amp	5.5 Kw	20 Amp	1NO or 1NC
MC16-10-3P-24VDC	24 VDC	16 Amp	7.5 Kw	20 Amp	1NO or 1NC
MC16-10-3P-110VDC	110 VDC	16 Amp	7.5 Kw	20 Amp	1NO or 1NC

