





GENERAL INFORMATION

pitch:	20 mm
housing height:	17,50 mm
housing depth:	16 mm
dimensional class:	medium
wire section:	2x2.5 mm ² / 2x14 AWG
clamp opening size:	
wire stripping:	max 11 mm
operating temperature:	-40°C ÷ +130°C

ELECTRICAL CHARACTERISTICS

current:	25A
voltage:	750V
test voltage:	3 kVrms/60s

MECHANICAL CHARACTERISTICS

screw:	M3.5
max. torque:	0.8 Nm / 7.2 in.lbs

APPROVALS DATA



EN 60998-1

current:	25A
voltage:	750V
wire section:	2x2.5mm ²
torque:	0.8Nm
FILE:	EQ203



EN 60998-1

25A
750V
2x2.5mm ²
0.8Nm
40019721



UL 1059

25A factory / 20A field
600V
12÷26AWG
7.2Lb-in
E178356

MATERIALS

housing:	PA - UL 94 V0
screw:	Galvanized steel
clamp/spring:	Galvanized iron
terminal:	Tin-plated copper alloy

AVAILABLE COLOURS



other colours: upon request

poles	P/N	pcs/pack	W [Kg]*	W [Kg]*
1	MT211-20-C	N/A	N/A	N/A
2	MT212-20-C	N/A	N/A	N/A
..	MT21..-20-C	N/A	N/A	N/A