




GENERAL INFORMATION

pitch:	10 mm
housing height:	10,60 mm
housing depth:	8.1 mm
dimensional class:	slow
wire section:	1.5 mm ² / 16 AWG
clamp opening size:	2.6 × 2 mm
wire stripping:	max 6 mm
operating temperature:	-40°C ÷ +130°C

ELECTRICAL CHARACTERISTICS

current:	13.5A
voltage:	750V
test voltage:	3 kVrms/60s

MECHANICAL CHARACTERISTICS

screw:	M3
max. torque:	0.5 Nm / 4.5 in.lbs

APPROVALS DATA



EN 60998-1



-



UL 1059

13.6A factory / 10A field

current:	13.5A
voltage:	750V
wire section:	1.5mm ²
torque:	0.5Nm
FILE:	EQ202

-

-

-

-

-

600V

16÷30AWG

4.5Lb-in

E178356

MATERIALS

housing:	PA - UL 94 V0
screw:	Galvanized steel
clamp/spring:	Nickeled copper alloy
terminal:	Tin-plated copper alloy

AVAILABLE COLOURS



other colours:

upon request

poles	P/N	pcs/pack	W [Kg]*	W [Kg]*
2	MV152-10-V-L	N/A	N/A	N/A
3	MV153-10-V-L	N/A	N/A	N/A
4	MV154-10-V-L	N/A	N/A	N/A
5	MV155-10-V-L	N/A	N/A	N/A
6	MV156-10-V-L	N/A	N/A	N/A