


MVP35x-15-V-KK euroclamp



GENERAL INFORMATION

pitch:	15 mm
housing height:	36,30 mm
housing depth:	32 mm
dimensional class:	high
wire section:	35 mm ² / 2 AWG
clamp opening size:	9 × 8.2 mm
wire stripping:	max 19 mm
operating temperature:	-40°C ÷ +130°C

ELECTRICAL CHARACTERISTICS

current:	125A
voltage:	1000V
test voltage:	2.5 kVrms/60s

MECHANICAL CHARACTERISTICS

screw:	M5
max. torque:	3 Nm / 27 in.lbs

APPROVALS DATA



	-	-	UL 1059
current:	-	-	125A factory / 125A field
voltage:	-	-	600V
wire section:	-	-	1÷20AWG
torque:	-	-	27Lb-in
FILE:	-	-	E178356

MATERIALS

housing:	PA - UL 94 V0
screw:	Galvanized steel

AVAILABLE COLOURS



clamp/spring:	Nickeled copper alloy	other colours:	upon request
terminal:	Tin-plated copper alloy		

poles	P/N	pcs/pack	W [Kg]*	W [Kg]*
1	MVP351-15-V-KK	N/A	N/A	N/A
..	MVP35..-15-V-KK	N/A	N/A	N/A