





GENERAL INFORMATION

pitch:	5 mm
housing height:	18,00 mm
housing depth:	11.2 mm
dimensional class:	medium
wire section:	2.5 mm ² / 14 AWG
clamp opening size:	2.8 × 3.5 mm
wire stripping:	max 9 mm
operating temperature:	-40°C ÷ +105°C

ELECTRICAL CHARACTERISTICS

current:	24A
voltage:	250V
test voltage:	2 kVrms/60s

MECHANICAL CHARACTERISTICS

screw:	M2.5
max. torque:	0.4 Nm / 3.5 in.lbs

APPROVALS DATA



current:	-	-	UL 1059
voltage:	-	-	20A factory / -A field
wire section:	-	-	300V
torque:	-	-	12÷24AWG
FILE:	-	-	3.5Lb-in
			E178356

MATERIALS

housing:	PA - UL 94 V0
----------	---------------

AVAILABLE COLOURS

screw: Galvanized steel  (STD)
 clamp/spring: Nickeled copper alloy other colours: upon request
 terminal: Tin-plated copper alloy

poles	P/N	pcs/pack	W [Kg]*	W [Kg]*
2	MVST252-5-V	N/A	N/A	N/A
3	MVST253-5-V	N/A	N/A	N/A
..	MVST25..-5-V	N/A	N/A	N/A