

MEASUREMENT & CONTROL

MECHANICAL TIME SWITCH

NAPA

- 2 Versions, Daily or Weekly
- Visual Time Display
- Surface, Panel or Din Rail Mount
- 16A Contact Rating
- Easy time adjustment
- Built in Battery Backup



Technical parameters	NAPA-D	NAPA-W
Function:	Daily Time Switch	Weekly Time Switch
Supply terminals:	1 & 2	
Supply voltage:	230VAC	
Power Consumption:	0.5VA	
Supply voltage tolerance:	+/- 10%	
Time ranges:	24 Hours	168 Hours
Time setting:	Captive Trippers	
Output		
Changeover contacts:	1	
Rated current:	16A	
Switching voltage:	Max. 250 VAC / 24 VDC	
Output indication:	-	
Operating Precision:	+/- 1s per day	
Controlling		
Control terminals:	3, 4 & 5	
Minimum Interval:	10 Minutes	1 Hour
Number of Trippers:	144	168
Other information		
Operating temperature:	-10 / +50°C	
Humidity:	85% RH	
Operating position:	Any	
Mounting:	Surface, Panel or Din Rail Mount	
Protection degree:	IP 20	
Dimensions:	72 x 72 x 47mm	
Charge Reserve:	200 hours after a 48 hour Charge	72 hours after a 48 hour Charge

NAPA-D / NAPA-W

