



NTFS IP65 4 Pole Metal Enclosed Fused Switch with Door Interlocked Handle




- 4 Pole (3P+ N) Fused Switch
- 32, 63, 80, 100 & 125 Amp
- AC21A 690VAC
- Weather proof to IP65
- Door Interlocked Handle
- Padlockable in Off position
- IP20 Protected terminals
- Supplied with Fuses
- Bottom Gland Plate
- 3P+N Rotary Isolator
- 3P Fuse Holder fitted with Fuses
- RAL7035 IP65 Steel enclosure
- Manufactured to IEC/EN 60947-3



TECHNICAL SPECIFICATION

Part Number	NTFS432	NTFS463	NFTS480	NTFS4100	NTFS4125
Poles	4 (3P+N)	4 (3P+N)	4 (3P+N)	4 (3P+N)	4 (3P+N)
Amperage	32 Amp	63 Amp	80 Amp	100 Amp	125 Amp
Rating	AC21A 690V (Resistive Loads)				
Isolator Make	SCL				
Isolator Part No.	NTF32-4	NTF63-4	NTF100-4	NTF100-4	NTF125-4
Fuse Holder Make	SCL				
Fuse Holder Part No.	DMS-103	DMS-223	DMS-223	DMS-223	DMS-223
Fuse Size	10x38	22x58	22x58	22x58	22x58
Fuse Amperage	32 Amp	63 Amp	80 Amp	100 Amp	125 Amp
IP Rating (Enclosure)	IP65				
IP Rating (Terminals)	IP20				
Enclosure	High quality Steel, Powder coated to RAL7035, with Bottom Gland Plate				
Enclosure Dimensions (mm)	300x200x150	400x300x150	400x300x150	400x300x150	400x300x150
Max. Tightening Torque (Main Switch)	1.2Nm	2.5Nm	2.5Nm	3.5Nm	3.5Nm
Max. Tightening Torque (Fuse Holder)	1.5Nm	3.5Nm	3.5Nm	3.5Nm	3.5Nm

WIRING DIAGRAM



Part of the NT Series of Switch Disconnectors, Switch Fuses & Change Over Switches available from Switchtec.

