





GENERAL INFORMATION

pitch:	5,08 mm
housing height:	28,82 mm
housing depth:	22.3 mm
dimensional class:	medium
wire section:	-
clamp opening size:	-
wire stripping:	-
operating temperature:	-40°C ÷ +130°C

ELECTRICAL CHARACTERISTICS

current:	10A
voltage:	500V
impulse voltage:	6 kV

MECHANICAL CHARACTERISTICS

APPROVALS DATA



EN 61984

current:	12A
voltage:	250V
FILE:	CA02.04178



EN 61984

12A
250V
40005779



UL 1059

12A factory / 12A field
300V
E178356

MATERIALS

housing:	PA - UL 94 V0
----------	---------------

AVAILABLE COLOURS

screw:

n/a



clamp/spring:

n/a

other colours:

upon request

terminal:

Tin-plated copper alloy

poles	P/N	pcs/pack	W [Kg]*	W [Kg]*
02	PDH02-5,08	N/A	N/A	N/A
03	PDH03-5,08	N/A	N/A	N/A
04	PDH04-5,08	N/A	N/A	N/A
05	PDH05-5,08	N/A	N/A	N/A
06	PDH06-5,08	N/A	N/A	N/A
07	PDH07-5,08	N/A	N/A	N/A
08	PDH08-5,08	N/A	N/A	N/A
09	PDH09-5,08	N/A	N/A	N/A
10	PDH10-5,08	N/A	N/A	N/A
11	PDH11-5,08	N/A	N/A	N/A
12	PDH12-5,08	N/A	N/A	N/A