



GENERAL INFORMATION

pitch:	5,08 mm
housing height:	19,00 mm
housing depth:	7.7 mm
dimensional class:	medium
wire section:	-
clamp opening size:	-
wire stripping:	-
operating temperature:	-40°C ÷ +105°C

ELECTRICAL CHARACTERISTICS

current:	12A
voltage:	250V
impulse voltage:	2 kV

MECHANICAL CHARACTERISTICS

APPROVALS DATA



current:
voltage:
FILE:

-
-
-

-
-
-

-
-
-

MATERIALS

housing:	PA - UL 94 V0
screw:	n/a
clamp/spring:	n/a
terminal:	n/a

AVAILABLE COLOURS



other colours:

upon request

poles	P/N	pcs/pack	W [Kg]*	W [Kg]*
02	PF02-5,08-V	N/A	N/A	N/A
03	PF03-5,08-V	N/A	N/A	N/A
04	PF04-5,08-V	N/A	N/A	N/A
05	PF05-5,08-V	N/A	N/A	N/A
06	PF06-5,08-V	N/A	N/A	N/A
07	PF07-5,08-V	N/A	N/A	N/A
08	PF08-5,08-V	N/A	N/A	N/A
09	PF09-5,08-V	N/A	N/A	N/A
10	PF10-5,08-V	N/A	N/A	N/A
11	PF11-5,08-V	N/A	N/A	N/A
12	PF12-5,08-V	N/A	N/A	N/A
13	PF13-5,08-V	N/A	N/A	N/A
14	PF14-5,08-V	N/A	N/A	N/A
15	PF15-5,08-V	N/A	N/A	N/A
16	PF16-5,08-V	N/A	N/A	N/A
17	PF17-5,08-V	N/A	N/A	N/A
18	PF18-5,08-V	N/A	N/A	N/A
19	PF19-5,08-V	N/A	N/A	N/A
20	PF20-5,08-V	N/A	N/A	N/A
21	PF21-5,08-V	N/A	N/A	N/A
22	PF22-5,08-V	N/A	N/A	N/A
23	PF23-5,08-V	N/A	N/A	N/A
24	PF24-5,08-V	N/A	N/A	N/A