





GENERAL INFORMATION

pitch:	10 mm
housing height:	8,50 mm
housing depth:	12.2 mm
dimensional class:	medium
wire section:	-
clamp opening size:	-
wire stripping:	-
operating temperature:	-40°C ÷ +130°C

ELECTRICAL CHARACTERISTICS

current:	15A
voltage:	500V
impulse voltage:	6 kV

MECHANICAL CHARACTERISTICS

APPROVALS DATA



EN 61984

current:	15A
voltage:	500V
FILE:	CA02.04178



EN 61984

current:	15A
voltage:	500V
FILE:	40005779



UL 1059

current:	12A factory / 12A field
voltage:	600V
FILE:	E178356

MATERIALS

housing:	PA - UL 94 V0
screw:	n/a
clamp/spring:	n/a
terminal:	Tin-plated copper alloy

AVAILABLE COLOURS



other colours: upon request

poles	P/N	pcs/pack	W [Kg]*	W [Kg]*
-------	-----	----------	---------	---------

02	PV02-10-H	N/A	N/A	N/A
03	PV03-10-H	N/A	N/A	N/A
04	PV04-10-H	N/A	N/A	N/A
05	PV05-10-H	N/A	N/A	N/A
06	PV06-10-H	N/A	N/A	N/A
07	PV07-10-H	N/A	N/A	N/A
08	PV08-10-H	N/A	N/A	N/A
09	PV09-10-H	N/A	N/A	N/A
10	PV10-10-H	N/A	N/A	N/A
11	PV11-10-H	N/A	N/A	N/A
12	PV12-10-H	N/A	N/A	N/A