



Audible Alarms

Sonartone Series Panel Mount Audible Alarms



- Continuous, Pulsating or Siren sound outputs
- 95dB Max sound output
- Sealed construction to an IP65 level
- AC & DC Models up to 240VAC
- Solid state circuitry
- No RF noise & low power consumption
- -30°C to +60°C
- CE approved
- Panel cut out 29mm

Part Number	Voltage	Operating Voltage	Frequency Hz	Tone
SC-01-416	12VDC	4-16VDC	2900 +/-500	Continuous
SP-01-416	12VDC	4-16VDC	2900 +/-500	Pulsating
SW-01-416	12VDC	6-15VDC	500-4000	Siren
SC-01-428	24VDC	4-28VDC	2900 +/-500	Continuous
SP-01-428	24VDC	4-28VDC	2900 +/-500	Pulsating
SX-01-428	24VAC/DC	4-28VAC/DC	2900 +/-500	Continuous
SY-01-428	24VAC/DC	4-28VAC/DC	2900 +/-500	Pulsating
SD-02-428	24VDC	4-28VDC	2900 +/-500	Dual Continuous - Pulsating
SC-03-115	110VAC	30-120VAC/DC	2900 +/-500	Continuous
SP-03-115	110VAC	30-120VAC/DC	2900 +/-500	Pulsating
SC-03-250	240VAC	90-250VAC	2900 +/-500	Continuous
SP-03-250	240VAC	90-250VAC	2900 +/-500	Pulsating

Other voltages available

Stridor Series Multi Tone Alarm



- 32 Selectable tones
- High sound output up to 102dB
- Built in volume control
- Multi voltage, 9-28VDC & 15-30VAC/CD & 110-240VAC versions
- Primary & secondary tone via 3rd terminal
- IP65 Surface mount (Deep Base models)
- Low power consumption & simple wiring
- CE approved
- Available with Shallow or Deep Base
- Available in Red or White

Part Number	Description
SMS-01-RED ●	9-28VDC Surface Mount Alarm with Shallow Base IP54 Red
SMS-01-WHITE ○	9-28VDC Surface Mount Alarm with Shallow Base IP54 White
SMS-01-VA-RED ●	15-30VAC/DC Surface Mount Alarm with Shallow Base IP54 Red
SAU-04-VC-RED ●	110-250VAC Surface Mount Alarm with Deep Base IP65 Red
SAU-04-VC-WHITE ○	110-250VAC Surface Mount Alarm with Deep Base IP65 White

*Shallow base IP54. Fitting a deep base increases the IP rating to IP65
Deep Bases available as an accessory. Contact sales for further details.