


Data sheet:

REVERSING SWITCH 3P REF.T102 SIZE 0

telergon
gorlan team



Technical information



According to IEC/EN 60947-3
UL508 - CAN/CSA C22.2 N° 14

According to IEC 60947-3			TP10	T12	T20	TB20	TB25	TB32	TF12	TF16	TF25
Rated thermal current	Ith	A	12	16	25	20	25	32	20	25	32
Rated insulation voltage	Ui	V	500	500	500	500	500	500	690	690	690
Rated impulse withstand voltage	Uimp	kV	4	6	6	6	6	6	6	6	6
AC rated operational current	Ie	Ue 415V AC13A	A	10	-	-	-	-	-	-	-
		Ue 415V AC21A	A	12	16	25	20	25	32	20	25
		Ue 415V AC22A	A	12	16	25	20	25	32	20	25
		Ue 415V AC23A	A	10	-	-	20	25	32	-	-
		Ue 500V AC21A	A	-	16	20	20	25	32	-	-
		Ue 500V AC22A	A	-	16	20	20	25	32	-	-
		Ue 500V AC23A	A	-	-	-	16	20	25	-	-
		Ue 690V AC21A	A	-	-	-	-	-	16	25	32
		Ue 690V AC22A	A	-	-	-	-	-	16	25	25
		Ue 690V AC23A	A	-	-	-	-	-	16	25	25
AC rated operational power (Rated operational frequency 50/60 Hz)	Pe	3x240V AC3	kW	3	4	4	5,4	6,7	8,6	4	5,5
		3x240V AC3	kW	2,2	3	4	3,7	4,6	5,9	4	5,5
		3x240V AC4	kW	-	1,1	1,5	2,9	3,7	4,6	1,5	2,2
		1x240V AC3	kW	-	1,5	2,2	2,1	2,7	4	2,2	3
		1x240V AC4	kW	-	0,37	0,55	1	1,25	1,5	0,55	0,75
		3x415V AC23A	kW	4,6	5,5	7,5	9,3	11,7	15	7,5	11
		3x415V AC3	kW	4	4	5,5	6,4	8	10,3	5,5	7,5
		3x415V AC4	kW	-	2,2	3	3,1	3,8	5,5	3	4
		1x400V AC3	kW	-	2,2	3	3,6	4,5	5,7	3	4
		1x400V AC4	kW	-	0,75	1,1	1,7	2,2	3	1,1	1,5
		3x500V AC23A	kW	-	5,5	7,5	9	11	14	7,5	11
		3x500V AC3	kW	-	4	7,5	7,8	9,7	12,5	7,5	11
		3x500V AC4	kW	-	2,2	3	3,3	4,7	5,5	3	4
		3x690V AC23A	kW	-	-	-	-	-	7,5	11	15
		3x690V AC3	kW	-	-	-	-	-	5,5	7,5	11
		3x690V AC4	kW	-	-	-	-	-	3	4	5,5
Rated conditional short-circuit current		kA	5	10	10	5	5	5	5	5	5
Rated maximum current	gL-gG	A	16	25	25	35	35	35	20	25	32
Rated breaking capacity	400V; cos φ=0,45	A	80	80	100	160	200	256	100	160	200
Rated short-time withstand current (1 sec)		A	100	240	400	240	400	500	350	400	500
Mechanical durability (thousand of operations)			2000	1000	1000	1000	1000	1000	1000	1000	1000
Rigid copper conductor	mm²	2x4	2x4	2x4	1x10 2x6	1x10 2x6	1x10 2x6	1x10 2x6	1x10	1x10	1x10
Flexible copper conductor	mm²	2x2,5	2x2,5	2x2,5	1x6 2x4	1x6 2x4	1x6 2x4	1x6 2x4	1x6	1x6	1x6
According to UL508 - CAN / CSA C22.2 N° 14				T12	T20				TF12	TF16	TF25
Rated thermal current	Ith	A		12	20	-	-	-	16	20	25
General use rating		Vac		300	300	-	-	-	600	600	600
AC rated operational power	3x240V	HP		2	5	-	-	-	2	5	7,5
	3x480V	HP		-	-	-	-	-	5	10	12
	3x600V	HP		-	-	-	-	-	5	10	15



You will find detailed information about our products on our web site www.telergon.es




CAM SWITCH
T-00XXX00102E1N1

TELERGON, S.A.U.
Data subject to change without
notice (printed: 23/05/2018)

Dimensions (mm)



TP series	Chambers	1	2	3	4
	H1	26,8	36,3	45,8	55,3






TB series	Chambers	1	2	3	4
	H3	31,5	41,5	51,5	61,5


E

Frontal fixing with 2 screws
TB T - TF

Frontal fixing with 4 screws
T - TB - TF - TP






T series	Chambers	1	2	3	4
	L1	34,5	46	57,5	69
	H2	37,5	49	60,5	72



TF series	Chambers	1	2	3	4
	L2	45	55	65	75
	H4	48	58	68	78

C

Frontal fixing
Ø22
T - TB - TF



You will find detailed information about our products on our web site www.telergon.es



CAM SWITCH
T-00XXX00102E1N1

TELERGON, S.A.U.
Data subject to change without
notice (printed: 23/05/2018)