



GENERAL INFORMATION

| | |
|------------------------|----------------|
| pitch: | 3,5 mm |
| housing height: | 9,20 mm |
| housing depth: | 7.25 mm |
| dimensional class: | slow |
| wire section: | - |
| clamp opening size: | - |
| wire stripping: | - |
| operating temperature: | -40°C ÷ +130°C |

ELECTRICAL CHARACTERISTICS

| | |
|------------------|--------|
| current: | 8A |
| voltage: | 160V |
| impulse voltage: | 2.5 kV |

MECHANICAL CHARACTERISTICS

APPROVALS DATA



| | | | |
|----------|---|---|-----------------------|
| current: | - | - | UL 1059 |
| voltage: | - | - | 8A factory / 8A field |
| FILE: | - | - | 300V |
| | | | E178356 |

MATERIALS

| | |
|---------------|---------------|
| housing: | PA - UL 94 V0 |
| screw: | n/a |
| clamp/spring: | n/a |

AVAILABLE COLOURS



other colours: upon request

terminal:

Tin-plated copper alloy

| poles | P/N | pcs/pack | W [Kg]* | W [Kg]* |
|-------|------------|----------|---------|---------|
| 02 | PV02-3,5-V | N/A | N/A | N/A |
| 03 | PV03-3,5-V | N/A | N/A | N/A |
| 04 | PV04-3,5-V | N/A | N/A | N/A |
| 05 | PV05-3,5-V | N/A | N/A | N/A |
| 06 | PV06-3,5-V | N/A | N/A | N/A |
| 07 | PV07-3,5-V | N/A | N/A | N/A |
| 08 | PV08-3,5-V | N/A | N/A | N/A |
| 09 | PV09-3,5-V | N/A | N/A | N/A |
| 10 | PV10-3,5-V | N/A | N/A | N/A |
| 11 | PV11-3,5-V | N/A | N/A | N/A |
| 12 | PV12-3,5-V | N/A | N/A | N/A |
| 13 | PV13-3,5-V | N/A | N/A | N/A |
| 14 | PV14-3,5-V | N/A | N/A | N/A |
| 15 | PV15-3,5-V | N/A | N/A | N/A |
| 16 | PV16-3,5-V | N/A | N/A | N/A |
| 17 | PV17-3,5-V | N/A | N/A | N/A |
| 18 | PV18-3,5-V | N/A | N/A | N/A |
| 19 | PV19-3,5-V | N/A | N/A | N/A |
| 20 | PV20-3,5-V | N/A | N/A | N/A |
| 21 | PV21-3,5-V | N/A | N/A | N/A |
| 22 | PV22-3,5-V | N/A | N/A | N/A |
| 23 | PV23-3,5-V | N/A | N/A | N/A |
| 24 | PV24-3,5-V | N/A | N/A | N/A |