




Version with antirotation pegs is available on 2 poles connections.
Disponibile per connessioni a 2 poli versioni con perni antitorsione.

GENERAL INFORMATION

pitch:	5 mm
housing height:	16,30 mm
housing depth:	17 mm
dimensional class:	medium
wire section:	2.5 mm ² / 14 AWG
clamp opening size:	2.8 × 2.8 mm
wire stripping:	max 8 mm
operating temperature:	-40°C ÷ +130°C

ELECTRICAL CHARACTERISTICS

current:	16A
voltage:	450V
test voltage:	2.5 kVrms/60s

MECHANICAL CHARACTERISTICS

screw:	M3
max. torque:	0.5 Nm / 4.5 in.lbs

APPROVALS DATA



EN 60998-1

current:	16A
voltage:	450V
wire section:	2.5mm ²
torque:	0.5Nm
FILE:	EP149



EN 60998-1

16A
450V
2.5mm ²
0.5Nm
40023956



UL 1059

16A factory / 15A field
300V
14÷30AWG
4.5Lb-in
E178356

MATERIALS

housing:	PA - UL 94 V0
screw:	Galvanized steel

AVAILABLE COLOURS



clamp/spring: Nickeled copper alloy other colours: upon request
terminal: Tin-plated copper alloy

poles	P/N	pcs/pack	W [Kg]*	W [Kg]*
2	MI252-5-IQ	N/A	N/A	N/A
3	MI253-5-IQ	N/A	N/A	N/A
..	MI25..-5-IQ	N/A	N/A	N/A