




GENERAL INFORMATION

pitch:	10 mm
housing height:	13,50 mm
housing depth:	8.3 mm
dimensional class:	slow
wire section:	1.5 mm ² / 16 AWG
clamp opening size:	2.6 × 2.6 mm
wire stripping:	max 7 mm
operating temperature:	-40°C ÷ +130°C

ELECTRICAL CHARACTERISTICS

current:	17.5A
voltage:	750V
test voltage:	3 kVrms/60s

MECHANICAL CHARACTERISTICS

screw:	M2.5
max. torque:	0.4 Nm / 3.6 in.lbs

APPROVALS DATA



EN 60998-1



EN 60998-1



UL 1059

current:	17.5A
voltage:	750V
wire section:	1.5mm ²
torque:	0.4Nm
FILE:	EP151

17.5A
750V
1.5mm ²
0.4Nm
40019705

17.5A factory / 10A field
600V
16÷30AWG
3.6Lb-in
E178356

MATERIALS

housing:	PA - UL 94 V0
screw:	Galvanized steel
clamp/spring:	Tin-plated copper alloy

AVAILABLE COLOURS



other colours:

upon request

terminal:

Tin-plated copper alloy

poles	P/N	pcs/pack	W [Kg]*	W [Kg]*
2	MVE152-10-V-L	N/A	N/A	N/A
3	MVE153-10-V-L	N/A	N/A	N/A
4	MVE154-10-V-L	N/A	N/A	N/A
5	MVE155-10-V-L	N/A	N/A	N/A
6	MVE156-10-V-L	N/A	N/A	N/A
..	MVE15..-10-V-L	N/A	N/A	N/A