




GENERAL INFORMATION

pitch:	20,32 mm
housing height:	29,30 mm
housing depth:	17.25 mm
dimensional class:	high
wire section:	10 mm ² / 8 AWG
clamp opening size:	5.4 × 5.8 mm
wire stripping:	max 15 mm
operating temperature:	-40°C ÷ +130°C

ELECTRICAL CHARACTERISTICS

current:	57A
voltage:	750V
test voltage:	3 kVrms/60s

MECHANICAL CHARACTERISTICS

screw:	M4
max. torque:	1.2 Nm / 10.8 in.lbs

APPROVALS DATA



-



EN 60998-1
70A
1000V
16mm²
1.5Nm
40034945



UL 1059
57A factory / 57A field
600V
6÷30AWG
10.8Lb-in
E178356

current:	-
voltage:	-
wire section:	-
torque:	-
FILE:	-

MATERIALS

housing:	PA - UL 94 V0
screw:	Galvanized steel

AVAILABLE COLOURS



clamp/spring:	Nickeled copper alloy	other colours:	upon request
terminal:	Tin-plated copper alloy		

poles	P/N	pcs/pack	W [Kg]*	W [Kg]*
1	MV101-20,32-V	N/A	N/A	N/A
2	MV102-20,32-V	N/A	N/A	N/A
..	MV10..-20,32-V	N/A	N/A	N/A